

# Enclosure

46-425.1400

Distribution by  
Mouser



<https://www.mouser.eao.com/component/46-425.1...>

Your product:

---



## 46-425.1400 Enclosure

*Loading ...*

### FRONT

**Colour:** Yellow

### MOUNTING

**Mounting cut-out:** Ø 22.3 mm

**Mounting type:** Panel mounting

### ELECTRICAL CHARACTERISTICS

**Pollution degree:** 3

**Protection class:** II, according to EN / IEC 61140

### MECHANICAL CHARACTERISTICS

**Tightening torque:** 0.8 ... 1.2 Nm (7.1÷10.6 Lb-in)

**Weight:** 0.125 kg

### AMBIENT CONDITION

**IP front protection:** IP66

**IK front protection:** IK07

**Operating temperature:** – 35 °C ... + 80 °C

### CERTIFICATE

**Approbations:** CSA, UL

**Conformities:** CE

**REACH:** REACH compliant  
**RoHS:** RoHS compliant  
**Standards:** CSA C22-2, IEC EN 60947-1, IEC EN 60947-5-1, UL508

**OTHER**

**Short Description:** Enclosure  
**Number of holes:** 1  
**Dimension:** 84 mm x 84 mm x 55 mm  
**Material:** Plastic  
**Product attributes:** Suitable for outdoor applications  
**max. number of switching elements:** 2  
**Dimension drawings:**

