

# Pendant control

46-445.1818

Distribution by  
Mouser



<https://www.mouser.eao.com/component/46-445.1...>

Your product:

---



## 46-445.1818 Pendant control

*Loading ...*

### FRONT

**Colour:** Grey

### MOUNTING

**Number of holes:** 1  
**Mounting cut-out:** Ø 22 mm  
**Mounting type:** Panel mounting

### ELECTRICAL CHARACTERISTICS

**Rated insulation voltage  $U_i$ :**  $U_i$  300V -  $U_{imp}$  2.5KV (IEC-EN60947-1)  
**Pollution degree:** 3  
**Protection class:** II, according to EN / IEC 61140

### MECHANICAL CHARACTERISTICS

**Tightening torque:** 0.8 ... 1.2 Nm (7.1÷10.6 Lb-in)  
**Weight:** 0.2 kg

### AMBIENT CONDITION

**IP front protection:** IP65, IP66  
**IK front protection:** IK08  
**Operating temperature:** - 35 °C ... + 80 °C

### CERTIFICATE

|                      |  |
|----------------------|--|
| <b>Approbations:</b> | CSA, UL  |
| <b>Conformities:</b> | CE   |
| <b>REACH:</b>        | REACH compliant  |
| <b>RoHS:</b>         | RoHS compliant   |
| <b>Standards:</b>    | CSA C22-2, IEC EN 60204-1, IEC EN 60947-1, IEC EN 60947-5-1, UL508 |

**OTHER**

|                            |                                   |
|----------------------------|-----------------------------------|
| <b>Short Description:</b>  | Pendant control                   |
| <b>Dimension:</b>          | 83 mm x 137 mm                    |
| <b>Housing material:</b>   | Plastic                           |
| <b>Product attributes:</b> | Suitable for outdoor applications |
| <b>Dimension drawings:</b> |                                   |

