

Pendant control

46-457.1818

Distribution by
Mouser



<https://www.mouser.eao.com/component/46-457.1...>

Your product:



46-457.1818 Pendant control

Loading ...

FRONT

Colour: Grey

MOUNTING

Mounting cut-out: Ø 22 mm

Mounting type: Panel mounting

ELECTRICAL CHARACTERISTICS

Rated insulation voltage U_i : U_i 300V - U_{imp} 2.5KV (IEC-EN60947-1)

Pollution degree: 3

Protection class: II, according to EN / IEC 61140

MECHANICAL CHARACTERISTICS

Tightening torque: 0.8 ... 1.2 Nm (7.1÷10.6 Lb-in)

Weight: 0.4 kg

AMBIENT CONDITION

IP front protection: IP65, IP66

IK front protection: IK08

Operating temperature: - 35 °C ... + 80 °C

CERTIFICATE

Approbations: CSA, UL

Conformities: CE
REACH: REACH compliant
RoHS: RoHS compliant
Standards: CSA C22-2, IEC EN 60204-1, IEC EN 60947-1, IEC EN 60947-5-1, UL508

OTHER

Short Description: Pendant control
Number of holes: 3 (2+1)
Dimension: 83 mm x 197 mm
Housing material: Plastic
Product attributes: Suitable for outdoor applications
Dimension drawings:

