

# Pendant control

46-458.1418

Distribution by  
Mouser



<https://www.mouser.eao.com/component/46-458.1...>

Your product:

---



## 46-458.1418 Pendant control

*Loading ...*

### FRONT

**Colour:** Yellow

### MOUNTING

**Number of holes:** 4

**Mounting cut-out:** Ø 22 mm

**Mounting type:** Panel mounting

### ELECTRICAL CHARACTERISTICS

**Pollution degree:** 3

**Protection class:** II, according to EN / IEC 61140

### MECHANICAL CHARACTERISTICS

**Tightening torque:** 0.8 ... 1.2 Nm (7.1÷10.6 Lb-in)

**Weight:** 0.4 kg

### AMBIENT CONDITION

**IP front protection:** IP65, IP66

**IK front protection:** IK07

**Operating temperature:** – 35 °C ... + 80 °C

### CERTIFICATE

**Approbations:** CSA, UL

<b>Conformities:</b>	CE
<b>REACH:</b>	REACH compliant
<b>RoHS:</b>	RoHS compliant
<b>Standards:</b>	CSA C22-2, IEC EN 60204-1, IEC EN 60947-1, IEC EN 60947-5-1, UL508

## OTHER

<b>Short Description:</b>	Pendant control
<b>Dimension:</b>	83 mm x 197 mm
<b>Housing material:</b>	Plastic
<b>Product attributes:</b>	Suitable for outdoor applications
<b>Dimension drawings:</b>	

