

# Pendant control

46-458.1818

Distribution by  
Mouser



<https://www.mouser.eao.com/component/46-458.1...>

Your product:

---



## 46-458.1818 Pendant control

*Loading . .*

### FRONT

**Colour:** Grey

### MOUNTING

**Number of holes:** 4  
**Mounting cut-out:** Ø 22 mm  
**Mounting type:** Panel mounting

### ELECTRICAL CHARACTERISTICS

**Rated insulation voltage  $U_i$ :**  $U_i$  300V -  $U_{imp}$  2.5KV (IEC-EN60947-1)  
**Pollution degree:** 3  
**Protection class:** II, according to EN / IEC 61140

### MECHANICAL CHARACTERISTICS

**Tightening torque:** 0.8 ... 1.2 Nm (7.1÷10.6 Lb-in)  
**Weight:** 0.4 kg

### AMBIENT CONDITION

**IP front protection:** IP65, IP66  
**IK front protection:** IK08  
**Operating temperature:** - 35 °C ... + 80 °C

### CERTIFICATE

<b>Approbations:</b>	CSA, UL
<b>Conformities:</b>	CE
<b>REACH:</b>	REACH compliant
<b>RoHS:</b>	RoHS compliant
<b>Standards:</b>	CSA C22-2, IEC EN 60204-1, IEC EN 60947-1, IEC EN 60947-5-1, UL508

**OTHER**

<b>Short Description:</b>	Pendant control
<b>Dimension:</b>	83 mm x 197 mm
<b>Housing material:</b>	Plastic
<b>Product attributes:</b>	Suitable for outdoor applications
<b>Dimension drawings:</b>	

