

# Illumination element, 24 V

46-580.1F21

Distribution by  
Mouser



<https://www.mouser.eao.com/component/46-580.1...>

Your product:

---



## 46-580.1F21 Illumination element, 24 V

*Loading ...*

### **MOUNTING**

**Mounting type:** Panel mounting

### **OPERATING-/INDICATION PART**

**Illumination colour:** Orange

### **ELECTRICAL CHARACTERISTICS**

**Operating voltage:** 24 V AC/DC -20% / +10%

**Protection class:** II, according to EN / IEC 61140

### **MECHANICAL CHARACTERISTICS**

**Weight:** 0.147 kg

### **AMBIENT CONDITION**

**IP front protection:** IP44

**IK front protection:** IK07

**Operating temperature:** - 25 °C ... + 65 °C

### **CERTIFICATE**

**Conformities:** CE

**Standards:** EN 55015, EN 61000-3-2, EN 61000-3-3, EN 61547, IEC EN 60947-1, IEC EN 60947-5-1, IEC EN 62471

## OTHER

<b>Short Description:</b>	Illumination element, 24 V, Ø 75 mm x 75 mm, Panel mounting, 24 V AC/DC -20% / +10%
<b>Titel Accessory:</b>	Illumination element, 24 V
<b>Dimension:</b>	Ø 75 mm x 75 mm
<b>Housing material:</b>	Plastic
<b>Product attributes:</b>	For Signal Light Tower