

Connection module

46-581.1800

Distribution by
Mouser



<https://www.mouser.eao.com/component/46-581.1...>

Your product:



46-581.1800 Connection module

FRONT

| | |
|--------------------|-------|
| Front form: | Round |
| Colour: | Grey |

MOUNTING

| | |
|-----------------------|----------------|
| Mounting type: | Panel mounting |
|-----------------------|----------------|

ELECTRICAL CHARACTERISTICS

| | |
|---|--|
| Rated insulation voltage U_i: | U_i 690V - U_{imp} 4KV (IEC-EN60947-1) |
| Pollution degree: | 3 |
| Protection class: | II, according to EN / IEC 61140 |

MECHANICAL CHARACTERISTICS

| | |
|----------------|----------|
| Weight: | 0.165 kg |
|----------------|----------|

AMBIENT CONDITION

| | |
|-------------------------------|---------------------|
| IP front protection: | IP44 |
| IK front protection: | IK07 |
| Operating temperature: | - 25 °C ... + 65 °C |

CERTIFICATE

| | |
|----------------------|-----------------|
| Conformities: | CE |
| REACH: | REACH compliant |

RoHS: RoHS compliant
Standards: IEC EN 60947-1, IEC EN 60947-5-1

OTHER

Short Description: Connection module, Round, IP44, IK07
Material: Plastic
Colour RAL: 7016 RAL